

# TECHNICAL DATA SHEET

## HOCUT® 4740

### WATER SOLUBLE METALWORKING FLUID

HOCUT® 4740 is advanced, high lubricity, boron-free and formaldehyde-free emulsion technology giving very long sump-life.

A special additive package gives greatly enhanced machining performance compared to conventional products and is particularly effective on difficult materials including aluminium, nickel and titanium alloys. .

#### Applications

HOCUT® 4740 is recommended for heavy duty machining of a wide range of materials including aluminium alloys, high alloy steels and difficult materials such as titanium and nickel alloys.

The product is suitable for both centralised systems and single-sump machines while the advanced boron-free technology extends emulsion life without the need for regular biocide treatments.

The versatile formulation is designed to give low foam in soft water.

#### Recommendation For Use

Medium duty machining 6-8 %

Heavy duty machining 8-10 %

#### Benefits

- High lubricity : sophisticated package of mineral oil and polar additives extend tool-life
- Very long sump-life : new HOCUT 4000 series emulsion technology extends intervals between clean outs
- Very stable emulsion : fewer additive treatments and lower usage costs
- Inhibits aluminium staining : can be used for sensitive alloys eg 7000 series
- Very low foaming : ideal for the highest speeds and pressures in soft water
- Excellent EHS profile : Boron, formaldehyde, chlorine and Phenol-free. Contains only TRGS 611 approved amines

#### Health, Safety And Handling

Please consult the Safety Data Sheet (SDS) for information on storage, safe handling and disposal. The conditions or methods of handling, storage, use and disposal of the product are beyond our reasonable control - we assume no liability for any ineffectiveness of the product or any injury or damage, arising out of or in connection with these conditions.

#### Typical Physical Properties

PROPERTY	TYPICAL VALUE	UNIT
Concentrate Appearance	Amber oil	
Specific Gravity @20°C	0,97	DIN 51757
Refractometer Factor	1,05	HIM 53
Emulsion Appearance	Translucent	
pH @6%	8.9-9.5	DIN 51369

All reasonable care has been taken to ensure this publication is accurate upon issue. Such information may be affected by changes subsequent to issue. This Technical Data Sheet is to be used solely for this product. Prior to any use, consult the Safety Data Sheet (SDS) for information on hazard risks and product use parameters. All liability and all warranties express or implied are hereby excluded as to product performance results, the accuracy of these data including any warranty of merchantability or fitness for any purpose. 42014740

